

MT1 LIGHT TOWER

MT1

The smallest mobile lighting tower equipped with built-in generator, the MT1 has been developed with the specific intent to be easily handled by a single operator, making it an ideal solution for illuminating small to medium sized working areas.



MT1 LED

MT1 RT-UFO

TECHNICAL DATA			
Minimum dimensions (mm)	Length x Width x Height	1100 x 1180 x 1900	2482 x 1318 x 2500
Maximum dimensions (mm)	Length x Width x Height	1630 x 2080 x 5300	2482 x 2280 x 5500
Dry weight (kg)		339	459
Lifting system	M:Manual / H:Hydraulic	M	M
Lamps power (W)		4 x 185	1 x 400
Lamps type	MH:MetalHalide / LD:LED	LD	LD
Total lumen (Lm)		93000	50000
Illuminated area (m²)	180° / 360°	2100 / n.a.	n.a. / 850
Engine		Yanmar L70N	Yanmar L70N
Engine cooling	L: Liquid / A: Air	A	A
Cylinders (q.ty)		1	1
Engine speed (RPM)	50 / 60 Hz	3000 / 3600	3000 / 3600
Liquid containment (110%)	√:Yes / ●:No	√	√
Alternator	kVA/V/Hz	5/220/50 - 5/240/60	5/220/50 - 5/240/60
Outlet Socket	kVA/V/Hz	2/220/50 - 2/240/60	2/220/50 - 2/240/60
Avg. sound pressure	dB(A) @ 7 m	68	68
Wind speed resistance (km/h)		80	80
Tank capacity (liters)		17	17
Total running time (h)		34	34
Standard trailer		Hand trolley	Road trailer

MT1 LIGHT TOWER

EASY HANDLING

The front steering handle combined with four wheels and a light weight ensure a large turning radius and easy transportation.

LAMP OPTIONS

Choose the lamp type you prefer between 4x185 LED or the innovative 400W UFO LED floodlights.



OPTIONS AVAILABLE

- Hand trolley (standard)
- Road trailer type E (straight)
- 110V outlet socket
- Earth picket with 5m cable
- Pre-heating system
- Ball hitch type 50 mm
- Eyelet hitch type 50 mm
- Plastic box for documents
- Dedicated colour
- Hot-dip zinc coating of mast sections
- Shut-off valve
- Certified spark arrestor
- Documents for EU road registration
- Schuko outlet socket (IP44)